

Laser illumination system



**Up to 400W
lighting power**

**660nm
wavelength**

**Flexible
triggering/
synchronisation**

The Specialised Imaging LUX2 laser illumination system provides up to 400W of lighting power at pulse frequencies up to 10MHz or single pulses up to 30 μ S.

Simple triggering allows the SI-LUX2 to interface with most high-speed cameras ranging from High-speed video to Ultra highspeed framing cameras.

The 2m laser output light guide includes user interchangeable low coherence beam expanders.

FEATURES

- Low coherence
- Pulse width from 10ns – 30 μ s
- Pulse frequency range from single to 10MHz
- Compact design

OPTICAL

Beam Expanders	φ25mm and φ50mm versions
Wavelength	660nm ± 10nm
Output power	200W (-10/ + 30%) or 400W (-10/ + 20%)
Power drop	~ 0.2% / μs for pulses less than 5μs

INPUT / OUTPUT SIGNALS

Sync. Input (BNC)	+5V TTL (laser pulse duration = duration of +5V state)
Indicators	Green LED – Laser is powered & ready
Electrical Input	Mains 100–240V AC 50–60Hz

SAFETY FEATURES

Laser rating	Class 3b
Safety features	Key operated master control power on/off Connector for remote Interlock Capping shutter on lens and laser head
Visual indicator	Green LED = Laser is powered & ready Red LED = interlock indicator Laser classification stated on unit

ENVIRONMENTAL

Storage temperature	-10°C to +50°C
Operating temperature	+10°C to +25°C
Humidity	10—90% RH non condensing
Vibration shock	10—40 Hz Max. 10g in any direction
EMC	Meets all UKCA/EU harmonised standards

TIMING PARAMETERS

Max pulse rate	10MHz
Min. single pulse duration	~10ns
Max. single pulse duration	30μs (max. power drop 20%)
Rise time	~10ns (10%..90%)
Fall time	~5ns
Delay	80ns ±10ns between input to start of light pulse (incl. control cable delay)
Jitter	<5ns
Operating limits	Max. 0.03% duty cycle for unlimited operation Max. 100% duty cycle for 30μs laser operation

MECHANICAL

Dimension (w/d/h)	Laser: 6.2cm x 15cm x 3.6cm (6" x 2.4" x 1.4") Master control box: 12cm x 6cm x 12cm (4.7" x 2.4" x 4.7")
Weight	Laser: 0.5Kg (1.1lbs) Master control box: 0.5Kg (1.1lbs)
Light guide	2m
Control cable	2m between control/safety box & laser

UK (Head Office / Factory)
6 Harvington Park,
Pitstone Green Business Park
Pitstone. LU7 9GX England
Tel +44 (0) 1442 827728

USA
Specialised Imaging Inc.
40935 County Center Dr. Suite D
Temecula, CA 92591, USA
Tel +1 951-296-6406

GERMANY
Bahnhofstr. 26 D,
82256 Fürstenfeldbruck,
Germany
Tel +49 8141 666 89 50



FM87429